

DMS

Dynamic Motion Sensors

Accurate motion measurement in all sea conditions

The DMS range of motion sensors is designed specifically for the motion measurement needs of the marine industry. Whether it is achieving IHO standard survey from any size of vessel, or providing safety critical monitoring of offshore platforms, large vessels, helicopter landing decks, cranes and positioning systems, the DMS provides accurate motion measurement in all sea conditions.

Incorporating an enhanced external velocity and heading aiding algorithm for improved accuracy during dynamic manoeuvres, the solid state angular rate sensors offer reliability in the highest performing vertical reference units ever produced by TSS.



Subsea



Surface

PRODUCT FEATURES AND BENEFITS

- Dynamic roll and pitch accuracy from 0.03° to 0.50° RMS
- Heave accuracy ±5cm or 5%
- Solid state solution available in surface or subsea housings
- Survey to Class 1 IHO standard
- High dynamic accuracy during vessel turns
- High reliability
- Power and data over Ethernet (surface units)
- Independently configurable serial outputs
- Complies with IEC 60945
- 24 hour, 365 days per year technical support
- Intuitive control software with user-configurable outputs
- Real-time digital and analogue outputs
- Compact and lightweight
- Low power, cost-effective solutions



TELEDYNE TSS
Everywhereyoulook™

DMS

Dynamic Motion Sensors

The DMS range of sensors is available in surface or subsea variants - the subsea unit is rated to 3000m as standard with 6000m available on request. As with all TSS systems, the DMS is certified to meet all current and anticipated European legislation for electromagnetic compatibility and electronic emissions.

The latest DMSView software programme is an intuitive Windows™ based programme enabling installation, set-up and integrity checking, and monitoring of the sensor. The user can select from a series of frequently used data protocols or configure a bespoke output from a selection of variables.

Product	Dynamic Accuracy	Depth Rating	Heave	Roll	Pitch
DMS-05	0.05°	✓	✓	✓	✓
DMS-10	0.10°	✓	✓	✓	✓
DMS-25	0.25°	✓	✓	✓	✓
DMS-RP25	0.25°	✓	x	✓	✓
DMS-RP30	0.30°	x	x	✓	✓
DMS-H	x	x	✓	x	x
DMS-525	0.25°	x	✓	✓	✓
DMS-525RP	0.25°	x	x	✓	✓
DMS-535RP	0.35°	x	x	✓	✓
DMS-550	0.50°	x	✓	✓	✓
DMS-550RP	0.50°	x	x	✓	✓
DMS-500H	x	x	✓	x	x

*Dynamic Accuracy at +/- 30°

No formal restrictions for most countries although heave products are subject to Export Licence.



Heave, Roll, Pitch

The DMS range of motion sensors is designed specifically for the motion measurement needs of the marine industry. Whether it is achieving IHO standard survey from any size of vessel, or providing safety critical monitoring of offshore platforms, large vessels, helicopter landing decks, cranes and positioning systems, the DMS provides accurate motion measurement in all sea conditions.

Incorporating an enhanced external velocity and heading aiding algorithm for improved accuracy during dynamic manoeuvres, the solid state angular rate sensors offer reliability in the highest performing vertical reference unit ever produced by TSS.



DMS-05 Subsea

PRODUCT FEATURES AND BENEFITS

- Dynamic roll and pitch accuracy to 0.03° (+/- 5°)
- Heave ±5cm
- Survey to Class 1 IHO standard
- High dynamic accuracy during vessel turns
- Surface and depth rated options available
- Real-time digital and analogue
- Compact and lightweight

Roll, Pitch

The DMS-RP sensors meet the requirements of the dynamic positioning industry for accurate vessel roll and pitch measurement. The units provide accurate motion measurement in all sea conditions.

Incorporating an enhanced external velocity and heading aiding algorithm for improved accuracy during dynamic manoeuvres, the solid state angular sensors offer reliability and a complimentary blending algorithm has proven that the DMS is the highest performance vertical reference unit ever produced by TSS.

The DMS-RP sensors are available in subsea and surface versions. The sensor can be supplied in various configurations for integration with towed vehicles and other bespoke applications.



DMS-RP25
Subsea

Heave

Whether in ports or harbours, offshore or as part of a hydrographic mapping programme, the need to measure ocean depths with the utmost accuracy is vital.

The DMS-500H heave sensor has been developed to work with a wide range of modern single beam echosounders. With their design, allowing acceptance of correction data from the DMS-500H, real-time heave compensation of the sounder data is achievable. Providing heave data in analogue and digital format, the outputs of the DMS-500H are easily configurable via a simple operator menu.

Compact, ruggedised and quick to install, the sensor is supplied with the cable connector necessary for interfacing and is accompanied by a comprehensive operation manual. In addition to echosounder compensation, the DMS-500H is ideally suited to a wide range of offshore applications including crane and winch control, wave radar and ship motion measurement.



DMS-500H
Surface

PRODUCT FEATURES AND BENEFITS

- Dynamic roll and pitch accuracy from 0.25° to 0.50° RMS
- Surface and subsea options available
- Independently configurable serial outputs
- Power and data over Ethernet (surface only)
- Survey to Class 1 IHO standard
- High dynamic accuracy during vessel turns
- DMSView intuitive control software
- User-configurable outputs
- Real-time digital outputs
- Compact and lightweight

PRODUCT FEATURES AND BENEFITS

- Measurement to meet IHO standards
- Provides cost savings by increasing weather windows for survey
- Solid state accelerometers and rate sensors
- Removes vertical motion errors from survey data to eliminate the need for post-processing
- Suitable for a wide variety of vessels
- IP 65 Rated
- Designed to provide operators with the optimum cost benefit solution
- Freephone telephone support for life of product

DMS

Dynamic Motion Sensors

TECHNICAL SPECIFICATIONS

	DMS-05	DMS-10	DMS-25	DMS-RP25	DMS-RP30	DMS-H	DMS-525	DMS-525RP	DMS-535RP	DMS-550	DMS-550RP	DMS-500H
PERFORMANCE												
Roll & Pitch °RMS												
+/- 5° Dynamic	0.03	0.06	0.15	0.25	0.30	N/A	0.05	0.25	0.35	0.10	0.50	N/A
+/- 30° Dynamic	0.05	0.10	0.25	0.25	0.30	N/A	0.25	0.25	0.35	0.50	0.50	N/A
Heave	5cm or 5%	5cm or 5%	5cm or 5%	N/A	N/A	5cm or 5%	5cm or 5%	N/A	N/A	5cm or 5%	N/A	5cm or 5%
Maximum Calibrated Range	Heave ±10m, Roll & Pitch ±30°						Heave ±10m, Roll & Pitch ±30°					
Data Resolution	Heave 1cm, Roll & Pitch 0.01						Heave 1cm, Roll & Pitch 0.01					
DATA OUTPUT RATE												
Digital	Up to 100Hz						Up to 100Hz					
Analogue	Up to 500Hz (with optional DMS repeater)						N/A					
PHYSICAL CHARACTERISTICS												
Dimensions	99mm (d) x 172mm (h) (excluding connector)						160mm x 160mm x 160mm (240mm max at base)					
Weight in Air	2.3kg (3000m), 4.0kg (6000m)				2.3kg	2.3kg	4.0kg					
Weight in Water	1.0kg (3000m), 2.7kg (6000m)				N/A	N/A	N/A					
Depth Rating	3000m standard, 6000m on request				3000m	3000m	N/A					
Power Supply	12 - 36Vdc (2A supply)						12 - 36Vdc (2A supply)					
Power Requirement	<6.5W						<12W					
Power Over Ethernet	N/A						IEEE 802.3AF-2003					
Temperature Range	-15°C to +55°C operating, -20°C to +70°C storage						-15°C to +55°C operating, -20°C to +70°C storage					
Shock (survival)	30g peak (40ms half sine)						30g peak (40ms half sine)					
Vibration (operating)	IEC 60945						IEC 60945					
INTERFACE FORMATS												
Sensor Aiding Velocity	NMEA0183 (VTG & GLL or GGA)						NMEA0183 (VTG & GLL or GGA)					
Sensor Aiding Heading	NMEA0183, SGB, Robertson; Sperry LR40/60						NMEA0183 (DMS-550)					
Output Data Formats	Industry Standard formats						Industry Standard formats					
INTERFACE												
Digital	RS232 or RS422 (software selectable)						RS232 or RS422 (software selectable), Ethernet					
Analogue	Via optional DMS repeater						Via optional DMS repeater					
Ethernet	N/A						Dual redundant frequencies. Packet output via TCP, UDP or UDP multicast					
Application Software	DMSView for Windows™						DMS500View for Windows™					
SYSTEM												
MTBF	50,000 hours											
Output Data Formats	24 months international warranty including parts and labour											
Export Compliance	Goods may be subject to export control. Details upon quotation											



TELEDYNE TSS
Everywhere you look™

www.teledynemarine.com/tss
Email: tssales@teledyne.com

Head Office

Teledyne Marine
ABZ Business Park, International Avenue, Dyce, Aberdeen AB21 0BH, UK
Tel: +44 (0)1224 772345
Fax: +44 (0)1224 772900



CE Specifications subject to change without notice.
© 2019 Teledyne Ltd. All rights reserved.